



Years Warranty*

ANSMANN ALCS 2-12/0.4

Lead acid charger for 2V, 6V and 12V lead acid, SLA batteries

Features

- Lead acid charger for 2V, 6V and 12V lead acid, SLA batteries
- With 3.5m charging cable
- Protection against short-circuit, wrong polarity and overcharge
- Suitable for standby and parallel mode
- Charging according to IU characteristic
- Automatic recharge, if the battery is left connected to the charger
- Ideal maintenance of lead acid batteries during winter time – no deep discharge
- Battery capacity: 1.2Ah - 40Ah
- Weight: only 135g due to modern switching power supply technology
- Operating voltage: 100V - 240V AC / 50Hz - 60Hz
- Charging current: 400mA



Voltage



Charging current



Overload protection



Cable length



Article number: 1001-0015
 Product content: ALCT 2-12/0.4 with pole terminals, cable 3,5m, manual
 Customs tariff number: 85044055900
 Packing Unit: 10 (295 × 175 × 185 mm)
 Price: 24,99 €



Specifications

Input voltage	100 - 240V AC
Max. output current	0,4 A
Battery voltage	2 V / 6 V / 12 V
Output	2V/6V/12: 400mA
suitable for	Lead Acid / SLA
Battery capacity from	1,2 Ah
Overload protection	Yes
Charge current control	Yes
Color	black
Packaging	cardboard box
Storage temperature	-25 - 70 °C
Operating temperature	0 - 25 °C