



Years Warranty*

ANSMANN PhotoCam Vario

Universal charger for Li-Ion/Li-Po battery packs (3.6V/3.7V or 7.2V/7.4V) or 2x 1.2V AA or AAA NiMH batteries

Features

- Universal charger for Li-Ion/Li-Po battery packs (3.6V/3.7V or 7.2V/7.4V) or 2x 1.2V AA or AAA NiMH batteries
- Incl. Micro USB charging cable and USB power adapter, with which USB devices can be charged separately (without using the PhotoCam Vario)
- Adjustable contacts for individual adaptation to most Li-Ion/Li-Po battery packs
- Automatic voltage and polarity detection for Li-Ion/Li-Po battery packs
- Charging starts automatically when a battery is connected
- Microprocessor controlled charging
- Short circuit protection, wrong polarity protection, faulty cell detection, safety timer
- Automatic battery full detection
- Trickle charge function for NiMH batteries
- Indication of the charging status via LED
- For worldwide use (100V-240V AC / 50-60Hz)
- Charging current: max. 600mA for Li-Ion/Li-Po, 1000mA for NiMH
- Ideal for travel, compact and lightweight



Charging current



Defect detection



Overload protection



Automatic Shutdown



Powered by USB



Article number: 1001-0019
 Product content: PhotoCam Vario, Micro USB charging cable 1m, USB charger 1A, manual
 Customs tariff number: 85044055900
 Packing Unit: 4 (150 × 150 × 280 mm)



Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride / Nickel-cadmium / Lithium
Chargeable cells	AAA / HR03 / AA / HR6 / battery pack / USB
Charging current AAA	1000 mA (2)
Charging current AA	1000 mA (2)
Charging current USB	1000 mA (5 V)
Ladestrom Lithium	600 mA (3,7 V) / 500 mA (7,4 V)
Microprocessor control	Yes
Safety timer	Yes
Overload protection	Yes
Battery defect detection	Yes
Color	black
Packaging	blister packaging
Operating temperature	0 - 25 °C
Storage temperature	-25 - 70 °C