



Years Warranty\*

## ANSMANN M250F

Professional torch with seamless and infinite focussing, incl. 3x ANSMANN alkaline AAA batteries, removable retaining clip and wrist strap

### Features

- High-quality 5W LED aluminium torch for professional use
- Uses the latest LED technology from CREE
- Optical zoom: Seamless and infinite focussing from a precise point of light to homogeneous floodlighting by turning the lamp head
- Microcontroller-managed tactical end-cap switch with four lighting functions: Boost/100%/30%/strobe and Morse function
- Non-slip exterior for maximum user comfort even when wearing gloves, ideal for single-handed use
- Brightness: 260 lumen (100%), 75 lumen (30%)
- Battery life ca. 3 h (100%), ca. 10 h (30%)
- Light range: Up to 150 m
- Protection: IP54 / impact resistance up to 1m drop height
- Includes 3x AAA alkaline batteries, removable belt clip and wrist strap
- Packaged in appealing hanging blister pack
- 3 year ANSMANN-Germany manufacturer's guarantee



High Power LED



Luminous flux



Brightness



Beam



Operating time



Seamless optic zoom



Aluminium housing



Splashproof



Article number: 1600-0171  
 Product content: Torch M250F, 3x Micro AAA batteries, lanyard, belt clip  
 Customs tariff number: 8513100000  
 Packing Unit: 6 (240 × 135 × 285 mm)  
 Price: 34,99 €



## Specifications

|                       |                     |                    |                      |                   |                       |
|-----------------------|---------------------|--------------------|----------------------|-------------------|-----------------------|
| Illuminant            | LED                 |                    |                      |                   |                       |
| Illuminant power      | 5 W                 |                    |                      |                   |                       |
| Light range           | 150 m               |                    |                      |                   |                       |
| Luminous flux         | 260 lumens          |                    |                      |                   |                       |
| Brightness            | 5.700 Lux           |                    |                      |                   |                       |
| Protection class      | IP54                |                    |                      |                   |                       |
| Operating time        | 10 h                |                    |                      |                   |                       |
| Power supply          | 3× Micro AAA / LR03 |                    |                      |                   |                       |
| Light modes           | 100% / 30% / Strobe |                    |                      |                   |                       |
| Performance data      | <b>Mode</b>         | <b>Light range</b> | <b>Luminous flux</b> | <b>Brightness</b> | <b>Operating time</b> |
|                       | 100%                | 150 m              | 260 lumens           | 5.700 Lux         | 3 h                   |
|                       | 30%                 | 100 m              | 75 lumens            | 2.500 Lux         | 10 h                  |
| Housing material      | Aluminium           |                    |                      |                   |                       |
| Color                 | black               |                    |                      |                   |                       |
| Packaging             | blister packaging   |                    |                      |                   |                       |
| Operating temperature | -10 - 25 °C         |                    |                      |                   |                       |
| Storage temperature   | -10 - 50 °C         |                    |                      |                   |                       |