



Years Warranty*

ANSMANN HS20R Pro

Professional LED portable spotlight with integrated rechargeable battery, various light functions, wall mounting and orange coloured filter disc

Features

- Professional mobile spotlight made from robust ABS plastic with integrated LED technology with very high lighting power – protection rating IP20
- Extremely bright with 3 LEDs (CREE LED) and a power of max. 20W.
- Permanently installed li-ion rechargeable battery (3.7V / 10,400mAh)
- Seamless dimming (incl. soft-start function), warning light function and separate selection of the light sources, which have been specially developed for close-range, medium-range and long-range.
- 1700lm, ca. 500m and 7h illumination time with simultaneous illumination of all three LEDs with 100% lighting power! Depending on the LED selection, illumination times of over 100 hours can be achieved.
- The flashing warning mode can run for 200 to almost 500 hours – depending on the LED selected.
- The extra powerful mounting magnet fastens the lamp to any metallic object.
- Can also be used as an emergency light by activating the mains failure function.
- Including charge cradle with wall bracket for simple mounting as well as orange filter disc for use as a warning light



Luminous flux



Beam




Operating time



Magnetic mounting



Rechargeable Li-Ion battery



Micro USB charging



Article number: 1600-0223

Product content: Lamp, charge station, wall plugs and screws, USB cable, coloured filter disc, operating instructions

Customs tariff number: 8513100000

Packing Unit: 6 (428 × 220 × 280 mm)

Price: 119,99 €



Specifications

Nominal voltage	3,7 V				
Nominal capacity	10400 mAh				
Light range	470 m				
Luminous flux	1.700 lumens				
Brightness	55.140 Lux				
Protection class	IP20				
Operating time	500 h				
Power supply	Akkupack				
Performance data	Mode	Light range	Luminous flux	Brightness	Operating time
	All LEDs	470 m	1.700 lumens	55.140 Lux	7 h
	Long range	470 m	950 lumens	55.140 Lux	7,25 h
	Medium range	100 m	450 lumens	2.500 Lux	10 h
	Short range	29 m	360 lumens	205 Lux	10 h
Illuminant	Mode	Illuminant	Illuminant power	Optical system	
	Short range	5 W Cree LED	5 W	Lens (wide-angle illumination)	
	Medium range	5 W Cree LED	5 W	Reflector lens (larger point focus)	
	Long range	10 W Cree LED	10 W	Reflector (smaller point focus)	
Housing material	Kunststoff und Aluminium				
Color	black / red				
Packaging	cardboard box				

Storage temperature	-10 - 60 °C
Operating temperature	-10 - 25 °C