



Years Warranty*

ANSMANN FL1600AC

20 W ANSMANN Luminary LED spotlight with integrated 180 cm cable and CEE 7/4 ("Schuko") plug for professional use – robust and very bright

Features

- ANSMANN Luminary BASE work floodlight with 20 W SMD LEDs and a lighting power of up to 1.600 lumens
- Extremely bright and homogeneously illuminated light for working in indoor and outdoor areas
- Integrated 1.8m long H07RN-F rubber cable for flexible use outdoors such as on construction sites, for moderate mechanical stresses.
- Splash-proof (IP54) - can be used indoors and out
- Robust aluminium and ABS housing – extremely shock-resistant
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- Versatile use thanks to the sturdy adjustment bracket - the adjustable support can be adjusted up to 80°, and the light head a full 360°!
- The spotlight is very compact when folded up thanks to the adjustable bracket - the carry handle also enables it to be comfortably carried to the desired place of use



Luminous flux



Brightness Levels



Beam Angle



Daylight Color



Splashproof



Cable length



Temperature Range



Inside & Outside Use



Article number: 1600-0278
 Product content: FL1600AC, operating instructions
 Customs tariff number: 8513100000
 Packing Unit: 6 (540 × 285 × 295 mm)



Specifications

Input voltage	230V AC
Illuminant	LED
Illuminant power	20 W
Light range	54 m
Luminous flux	1.600 lumens
Brightness	2.880 Lux
Protection class	IP54
IK Protection Class	IK05
Horizontal beam angle	110 °
Colour temperature	5000 k
Energy efficiency class	A+
Kabellänge	180 cm
Housing material	Aluminium
Color	blue / black
Packaging	cardboard box
Operating temperature	-20 - 50 °C
Storage temperature	-25 - 65 °C