



ANSMANN WFL800

Robust and compact ANSMANN Luminary LED wall spotlight with 10 W

Features

- ANSMANN Luminary Home floodlight for wall mounting with 10 W SMD LEDs and a lighting power of up to 800 lumens
- Very flat construction - housing made from robust aluminium and ABS – extremely shock-resistant
- Protection rating IP54 ensures dust and water protection, enabling use indoors and out
- Full power straight away thanks to the latest SMD LED technology
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- The angle of the spotlight can be adjusted vertically through 190° thus enabling the light to be placed at the desired location
- Integrated H05RN-F cable with a length of 20 cm for firm and flexible connection with low mechanical stresses in dry, damp and wet rooms



Luminous flux



Daylight Color



Vertically adjustable



Splashproof



Beam Angle



Installation height



Temperature Range



Inside & Outside Use



Article number: 1600-0280
 Product content: WFL800, operating instructions
 Customs tariff number: 8513100000
 Packing Unit: 6 (440 × 180 × 135 mm)
 Price: 14,99 €



Specifications

Input voltage	230V AC
Illuminant	LED
Illuminant power	10 W
Light range	38 m
Luminous flux	800 lumens
Brightness	1.140 Lux
Protection class	IP54
Operating time	24 h
IK Protection Class	IK05
Horizontal beam angle	110 °
Colour temperature	5000 k
Energy efficiency class	A+
Mounting height	max. 3 m
Housing material	Aluminium
Color	black
Packaging	cardboard box
Operating temperature	-20 - 50 °C
Storage temperature	-25 - 65 °C