



ANSMANN WFL1600S

Robust and compact 20 W ANSMANN Luminary LED wall spotlight with PIR movement detector

Features

- ANSMANN Luminary Sense floodlight for wall mounting with 20 W SMD LEDs and a lighting power of up to 1.600 lumens
- Integrated movement detector with a detection range of up to 12m and a detection angle of 180° horizontally and 90° vertically
- Adjustable lighting intensity - the lighting characteristics at which the floodlight should activate can be adjusted at any time
- The lighting time can be set from ca. 10 seconds to up to 10 minutes!
- Very flat construction - housing made from robust aluminium and ABS – extremely shock-resistant
- Protection rating IP54 ensures dust and water protection, enabling use indoors and out
- Full power straight away thanks to the latest SMD LED technology
- Very pleasant LED light with a colour temperature of 5000K (daylight)
- The angle of the spotlight can be adjusted vertically through 190° thus enabling the light to be placed at the desired location



Luminous flux



Daylight Color



Adjustable lighting duration



Beam Angle



Sensor range



**Einstellbare
Lichtverhältnisse**



Installation height



Splashproof



Article number: 1600-0284
Product content: WFL1600S, operating instructions
Customs tariff number: 8513100000
Packing Unit: 6 (320 × 233 × 235 mm)



Specifications

Input voltage	230V AC
Illuminant	LED
Illuminant power	20 W
Light range	54 m
Luminous flux	1.600 lumens
Brightness	2.880 Lux
Protection class	IP54
Operating time	24 h
IK Protection Class	IK05
Horizontal beam angle	110 °
Colour temperature	5000 k
Energy efficiency class	A+
Mounting height	max. 3 m
Control distance	max. 12 m
Housing material	Aluminium
Color	black
Packaging	cardboard box
Operating temperature	-20 - 50 °C
Storage temperature	-25 - 65 °C