



Years Warranty*

ANSMANN Powerbank 10Ah Type-C 18W PD

External rechargeable battery pack with Quick Charge 3.0, Type C and Power Delivery (PD) protocol and a capacity of 10000 mAh

Features

- Compact, handy and mobile external rechargeable battery pack with Quick Charge 3.0 and Type C 18W Power delivery (PD) technology. With 4× faster charging of compatible devices (80% in just 35 minutes). Capacity: 10000 mAh / 37 Wh
- Universally chargeable via the Type C (5-9V/2A) or the micro-USB port (5V/2A)
- Multi-Safe technology: Over-charging protection, deep discharge protection, overload protection and short-circuit protection
- Output:
 - Type C: (PD+QC3.0) 5-6V - 3.0A / 6-9V - 2.0A / 9-12V - 1.5A
 - USB 1/2: (QC3.0) 5-6V - 3.0A / 6-9V - 2.0A / 9-12V - 1.5A
 - Total: 18W (PD+QC3.0)
- 3 year ANSMANN-Germany manufacturer's guarantee



Output USB 3.0 & USB Type C



Input Micro USB & USB Type C



Ready to fly



Inclusive USB cable & Type C cable



Power Delivery



Quickcharge 3.0 compatible



Geprüfte Sicherheit



Article number: 1700-0115

Product content: Powerbank 10Ah Type-C 18W PD, micro-USB cable, type-C cable, operating instructions

Customs tariff number: 85076000900

Packing Unit: 4 (215 × 130 × 100 mm)



Specifications

Output voltage	5 - 12V DC			
Nominal voltage	3,7 V			
Input voltage	5 - 9V DC			
Ports	2x USB (QC3.0); 1x Typ-C (PD - In/Out); 1x Mirco USB			
Cell chemistry	Lithium polymer			
Nominal capacity	10000 mAh			
Charging cycles	500			
Max. output current	3 A			
Max. input current	2 A			
Charging currents	Mode	Voltage	Current	Power
	USB 1/2 (QC3.0)	5,0 V	3 A	15,0 W
	USB 1/2 (QC3.0)	9,0 V	2 A	18,0 W
	USB 1/2 (QC3.0)	12,0 V	1,5 A	18,0 W
	Type-C (PD)	5,0 V	3 A	15,0 W
	Type-C (PD)	9,0 V	2 A	18,0 W
	Type-C (PD)	12,0 V	1,5 A	18,0 W
Output ports	USB / USB type C			
Input ports	Micro USB / USB type C			
Energy	37 Wh			
Output	Output Type-C (PD): 5V - 3.0A / 9V - 2.0A / 12V - 1.5A			
	Output USB 1/2 (QC3.0): 5V - 3.0A / 9V - 2.0A / 12V - 1.5A			
	Total Output: 18W / 3.0A max.			
Color	anthracite			
Packaging	cardboard box			

Operating temperature

-20 - 25 °C