



ANSMANN Energy 8 plus

Years Warranty*

Charging and maintenance device for 1-6 Micro AAA / Mignon AA, 1-4 Baby C / Mono D and 1-2 9V E-Block rechargeable batteries, automatic refreshing function

Features

- Battery charging and maintenance device for 1-6 AAA or AA cells, 1-4 C or D cells and 1-2pcs 9V E-Block; suitable for NiCd and NiMH rechargeable batteries
- Charging currents: 1000mA for AA, C and D cells, 400mA for AAA cells and 60mA for 9V Blocks
- Capacity quick test of the inserted cells for approx. 5 seconds
- Auto-diagnosis of the inserted cells with automatic start of a refreshing process and/or pre-charging process, if required
- Microprocessor controlled charging & individual supervision of each cell position
- Five-way over charging protection
- Alkaline battery detection & faulty cell detection
- Trickle charge
- Switch mode power supply for world wide use (100-240V wide range input)



Overheat protection



Individually controlled



Overcharging protection (trickle charge)



Refresh



Defect detection



Capacity Quick Test



Article number: 5207442

Product content: Energy 8 plus, power cord 1,8m, manual

Customs tariff number: 85044055900

Packing Unit: 4 (296 × 278 × 222 mm)



Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride
Chargeable cells	AAA / HR03 / AA / HR6 / C / HR14 / D / HR20 / 9V block / 6F22
Charging current AAA	400mA (1-6)
Charging current AA	1000mA (1-6)
Charging current C	1000mA (1-4)
Charging current D	1000mA (1-4)
Charging current E	60mA (1-2)
Microprocessor control	Yes
Temperature monitoring	Yes
Safety timer	Yes
Single shaft monitoring	Yes
Overload protection	Yes
Refresh function	Yes
Battery defect detection	Yes
Kapazitäts-Schnelltest	Yes
Color	silver / blue
Packaging	cardboard box
Operating temperature	0 - 25 °C
Storage temperature	-25 - 70 °C