



Years Warranty*

ANSMANN PhotoCam V

Desktop charger for 1-4 Micro AAA / Mignon AA / Baby C / Mono D and 1x 9V E-Block rechargeable batteries, automatic battery-full-detection (-deltaV) for round cells

Features

- Intelligent charger for 1-4 NiMH or NiCd rechargeable cells in sizes Micro AAA, Mignon AA, Baby C, Mono D and one 9V E-Block
- Charging status indicator via LED
- Individual charging of each cell position
- Reverse polarity protection
- World wide use (100-240V AC / 50-60Hz)
- For round cells: Capacity quick test for approx. 5 seconds after inserting the cells,
- Microprocessor controlled charging
- Automatic charging current adjustment
- Multiple over-charging protection
- Trickle charging
- Faulty cell detection / accidental Alkaline insertion detection



Single Shaft Monitoring



Overload protection



Automatic Shutdown



Capacity Quick Test



Charging time (AA 1000mAh)



Article number: 5207473
 Product content: PhotoCam V, power cord 1,8m, manual
 Customs tariff number: 85044055900
 Packing Unit: 4 (255 × 230 × 295 mm)



Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride
Chargeable cells	AAA / HR03 / AA / HR6 / C / HR14 / D / HR20 / 9V block / 6F22
Charging current AAA	400 mA (1/2) 200 mA (3/4)
Charging current AA	800 mA (1/2) 400 mA (3/4)
Charging current C	800 mA (1/2) 400 mA (3/4)
Charging current D	800 mA (1/2) 400 mA (3/4)
Charging current E	15 mA (1)
Microprocessor control	only round cells
Safety timer	only round cells
Single shaft monitoring	only round cells
Overload protection	only round cells
Battery defect detection	only round cells
Quick capacity test	only round cells
Color	silver
Packaging	blister packaging