



ANSMANN PhotoCam IV + 4 Mignon NiMH batteries type 2500 (min. 2400) maxE Years Warranty*

Plug-in charger for 2 or 4 Micro AAA / Mignon AA rechargeable batteries, automatic battery-full-detection (-deltaV), LCD display, incl. 4x Mignon AA NiMH rechargeable batteries Type 2500

Features

- Intelligent charger for 2 or 4 NiMH/NiCd rechargeable batteries Mignon AA or Micro AAA
- Incl. 4x Mignon AA NiMH Type 2500 maxE batteries (minimum capacity 2400mAh)
- The charger has an illuminated display (LCD) which indicates the charging status of the batteries clearly
- over charging protection by -deltaV detection and safety timer
- faulty cell detection
- Alkaline insertion error detection
- reverse connect protection
- trickle charging
- wide range input 100-240V AC
- charging currents: AA 500mA, AAA 500mA
- 3 year warranty



Automatic Shutdown



Overload protection



LCD display



Charging time (AA 1000mAh)



Article number: 5317263

Product content: PhotoCam IV, manual, 4 AA rechargeable batteries maxE 2500mAh

Customs tariff number: 85044055900

Packing Unit: 4 (280 × 235 × 110 mm)



Specifications

Input voltage	100 - 240V AC
For worldwide use	Yes
Chargeable cell chemistry	Nickel metal hydride
Chargeable cells	AAA / HR03 / AA / HR6
Charging current AAA	500 mA (2/4)
Charging current AA	500 mA (2/4)
Microprocessor control	Yes
Safety timer	Yes
LCD display	Yes
Overload protection	Yes
Battery defect detection	Yes
Color	silver
Operating temperature	0 - 25 °C
Storage temperature	-20 - 40 °C