



Atomos Firmware Upgrade



Shogun Studio 2 Firmware Update Process

How to update:

- Download the latest version of AtomOS for Shogun Studio 2 and the Controller Update from atomos.com/support.
- Disconnect the power cable from the Shogun Studio 2.
- Unzip ATOMSGNST_x.x.zip and place the file ATOMSGNST.bin onto a USB flash drive. Connect the flash drive to the USB port of the back of the unit.
NOTE: The USB flash drive must be formatted as FAT32.
- Connect the power cable to the Shogun Studio 2.
- Near the USB port, a blue LED will begin flashing. It will take a few minutes for the Controller Update to complete. The unit will automatically start up once the update is complete.
- Confirm the update installed correctly by opening the unit Info page where it will display the Controller version number.
- Power off the Shogun Studio 2 and remove the USB flash drive.
- Unzip ATOMST2_X.X.zip and copy ATOMST2.FW onto an SSD.
- Place the SSD into the first unit and power up.
NOTE: Both units can be updated at once by copying ATOMST2.FW onto two SSDs and placing them into both caddies before powering up.
- AtomOS will begin updating.
- Remove the SSD before the update is complete and the update file will still be on the SSD.
- Once AtomOS has been updated on unit 1, power down.
- Place the SSD into unit 2 and power up and AtomOS will install.
- Once the update is complete, go the Info page on each unit. The latest version will be displayed on both displays if installed correctly.